

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 311000
Identification of the substance or mixture Quick Sanding Sealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Coating (Paint, Varnish).

Uses advised against:

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

distributor

Konig North America LLC
2800 Black Lake Place, Unit D
Philadelphia, PA 19154 (USA)

Telephone: 1-215-426-6216
Telefax: 1-215-464-2144

Dept. responsible for information:

laboratory Telephone: 1-215-426-6216
Only available during office hours: M-F 8:00am - 4:00pm

E-mail (competent person) brian@konigtouchup.com

1.4. Emergency telephone number

Emergency Contact: CHEMTREC 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 2 / 13

P312 to do. Continue rinsing.
P337 + P313 Call a POISON CENTER or doctor/physician if you feel unwell.
P410 + P412 If eye irritation persists: Get medical advice/attention.
P501 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container to industrial incineration plant.

contains:

n-butyl acetate

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Product description / chemical characterization

Description Aerosol

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
204-065-8 115-10-6 603-019-00-8	01-2119472128-37-xxxx dimethylether Flam. Gas 1 H220 / compressed gas H280	25 < 50
203-539-1 107-98-2 603-064-00-3	01-2119457435-35-xxxx 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	1 < 2,5
205-500-4 141-78-6 607-022-00-5	01-2119475103-46-xxxx ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	10 < 20
200-661-7 67-63-0 603-117-00-0	01-2119457558-25-xxxx propan-2-ol Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	2,5 < 3
203-550-1 108-10-1 606-004-00-4	01-2119473980-30-xxxx 4-methylpentan-2-one Flam. Liq. 2 H225 / Acute Tox. 4 H332 / Eye Irrit. 2 H319 / STOT SE 3 H335	10 < 20
918-668-5	01-2119455851-35-xxxx Hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H335 / STOT SE 3 H336 / Aquatic Chronic 2 H411	3 < 5
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-xxxx n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	10 < 20

Additional information

* Substance with a common (EC) occupational exposure limit value.

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 3 / 13

respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 4 / 13

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

TWA: 730 mg/m³; 200 ppm

STEL: 1460 mg/m³; 400 ppm

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m³; 100 ppm

STEL: 560 mg/m³; 150 ppm

4-methylpentan-2-one

INDEX No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

TWA: 208 mg/m³; 50 ppm

STEL: 416 mg/m³; 100 ppm

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m³; 150 ppm

STEL: 966 mg/m³; 200 ppm

propan-2-ol

INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

TWA: 999 mg/m³; 400 ppm

STEL: 1250 mg/m³; 500 ppm

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

TWA: 766 mg/m³; 400 ppm

STEL: 958 mg/m³; 500 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

DNEL long-term inhalative (systemic), Workers: 1894 mg/m³

DNEL long-term inhalative (systemic), Consumer: 471 mg/m³

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50,6 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m³

DNEL long-term inhalative (systemic), Workers: 369 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000 Quick Sanding Sealer
Print date 28.04.2016 Revision date 18.04.2016
Version 1.11 Issue date 18.04.2016

EN
Page 5 / 13

DNEL long-term oral (repeated), Consumer: 3,3 mg/kg
DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg
DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m³

ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL long-term dermal (systemic), Workers: 63 mg/kg
DNEL acute inhalative (local), Workers: 1468 mg/m³
DNEL acute inhalative (systemic), Workers: 1468 mg/m³
DNEL long-term inhalative (local), Workers: 734 mg/m³
DNEL long-term inhalative (systemic), Workers: 734 mg/m³
DNEL long-term oral (repeated), Consumer: 4,5 mg/kg
DNEL long-term dermal (systemic), Consumer: 37 mg/kg
DNEL acute inhalative (local), Consumer: 734 mg/m³
DNEL acute inhalative (systemic), Consumer: 734 mg/m³
DNEL long-term inhalative (local), Consumer: 367 mg/m³
DNEL long-term inhalative (systemic), Consumer: 367 mg/m³

propan-2-ol

INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

DNEL long-term dermal (systemic), Workers: 888 mg/kg
DNEL long-term inhalative (systemic), Workers: 500 mg/m³
DNEL long-term oral (repeated), Consumer: 26 mg/kg
DNEL long-term dermal (systemic), Consumer: 319 mg/kg
DNEL long-term inhalative (systemic), Consumer: 89 mg/m³

4-methylpentan-2-one

INDEX No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

DNEL long-term dermal (systemic), Workers: 11,8 mg/kg
DNEL acute inhalative (local), Workers: 208 mg/m³
DNEL acute inhalative (systemic), Workers: 208 mg/m³
DNEL long-term inhalative (local), Workers: 83 mg/m³
DNEL long-term inhalative (systemic), Workers: 83 mg/m³
DNEL long-term oral (repeated), Consumer: 4,2 mg/kg
DNEL long-term dermal (systemic), Consumer: 4,2 mg/kg
DNEL acute inhalative (local), Consumer: 155,2 mg/m³
DNEL acute inhalative (systemic), Consumer: 155,2 mg/m³
DNEL long-term inhalative (local), Consumer: 14,7 mg/m³
DNEL long-term inhalative (systemic), Consumer: 14,7 mg/m³

Hydrocarbons, C9, aromatics

EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg
DNEL long-term inhalative (systemic), Workers: 150 mg/m³
DNEL long-term oral (repeated), Consumer: 11 mg/kg
DNEL long-term dermal (systemic), Consumer: 11 mg/kg
DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute inhalative (systemic), Workers: 960 mg/m³
DNEL long-term inhalative (systemic), Workers: 480 mg/m³
DNEL acute inhalative (systemic), Consumer: 859,7 mg/m³
DNEL long-term inhalative (systemic), Consumer: 102,34 mg/m³

PNEC:

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

PNEC sediment, freshwater: 0,681 mg/kg
PNEC, Soil: 0,045 mg/kg
PNEC sewage treatment plant (STP): 160 mg/L

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L
PNEC sediment, freshwater: 41,6 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000 Quick Sanding Sealer
Print date 28.04.2016 Revision date 18.04.2016
Version 1.11 Issue date 18.04.2016

EN
Page 6 / 13

PNEC sediment, marine water: 4,17 mg/kg

ethyl acetate

INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

PNEC aquatic, freshwater: 0,26 mg/L

PNEC aquatic, marine water: 0,026 mg/L

PNEC sediment, freshwater: 1,25 mg/kg

PNEC sediment, marine water: 0,125 mg/kg

PNEC, Soil: 0,24 mg/kg

PNEC sewage treatment plant (STP): 650 mg/L

propan-2-ol

INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

PNEC aquatic, freshwater: 140,9 mg/L

PNEC aquatic, marine water: 140,9 mg/L

PNEC aquatic, intermittent release: 140,9 mg/L

PNEC sediment, freshwater: 552 mg/kg

PNEC sediment, marine water: 552 mg/kg

PNEC, Soil: 28 mg/kg

PNEC sewage treatment plant (STP): 2251 mg/L

PNEC Secondary Poisoning: 160 mg/kg

4-methylpentan-2-one

INDEX No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

PNEC aquatic, freshwater: 0,6 mg/L

PNEC aquatic, marine water: 0,06 mg/L

PNEC aquatic, intermittent release: 1,5 mg/L

PNEC sediment, freshwater: 8,27 mg/kg

PNEC sediment, marine water: 0,83 mg/kg

PNEC, Soil: 1,3 mg/kg

PNEC sewage treatment plant (STP): 27,5 mg/L

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L

PNEC aquatic, marine water: 0,018 mg/L

PNEC aquatic, intermittent release: 0,36 mg/L

PNEC sediment, freshwater: 0,981 mg/kg

PNEC sediment, marine water: 0,0981 mg/kg

PNEC, Soil: 0,0903 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (DGUV-R 112-190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Filtering device (full mask or mouthpiece) with filter: A

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 7 / 13

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties**

Appearance:

Physical state Aerosol
Colour refer to label
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	-41 °C	calculated.	
Ignition temperature in °C:	n.a.		
Lower explosion limit	2,4 Vol-%	calculated.	
Upper explosion limit	26,2 Vol-%	calculated.	
Vapour pressure at 20 °C:	2205,26 mbar	calculated.	
Density at 20 °C:	0,79 g/cm ³	calculated.	
Vapour density; Bulk density	n.a. kg/m ³		
Water solubility (g/L)	insoluble		
pH at 20 °C:	N.A.		
Viscosity at 20 °C	8 s 4 mm	DIN 53211	
Distribution coefficient (n-octanol / water) (log P O/W)	n.a.		
solvent content:			
Organic solvents:	90 Wt %		
Water:	0 Wt %		
Initial boiling point and boiling range	-25 °C	calculated.	
Melting point/freezing point	n.a. °C		
Evaporation rate	n.a. °C		
Auto-ignition temperature:	n.a. °C		
Decomposition temperature:	n.a. °C		

9.2. **Other information:**

Explosive properties not explosive.
Not oxidising.
Odour threshold: not determined
No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No known hazardous reactions.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides. Keine Entstehungsgefahr der oben angeführten Produkte bei sachgemäßem Umgang

SECTION 11: Toxicological information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 311000 Quick Sanding Sealer
Print date 28.04.2016 Revision date 18.04.2016
Version 1.11 Issue date 18.04.2016

EN
Page 8 / 13



dimethyl ether

oral, LD50, Rat: > 10000 mg/kg
Based on available data the classification criteria are not met.

1-methoxy-2-propanol

oral, LD50, Rat: 5000 mg/kg
dermal, LD50, Rabbit: 13500 mg/kg
inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)
Based on available data the classification criteria are not met.

ethyl acetate

oral, LD50, Rat: 5620 mg/kg
dermal, LD50, Rabbit: > 18000 mg/kg
inhalative (vapours), LC50, Rat: 56 mg/L (4 h)
Based on available data the classification criteria are not met.

propan-2-ol

oral, LD50, Rat: 5840 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: 13900 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 25 mg/L (6 h)
Method: OECD 403
Based on available data the classification criteria are not met.

4-methylpentan-2-one

oral, LD50, Rat: > 2193 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 2000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: (4 h)
Harmful by inhalation.

Hydrocarbons, C9, aromatics

oral, LD50, Rat: 3592 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 3160 mg/kg
Method: OECD 402
Based on available data the classification criteria are not met.

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg
Method: OECD 423
dermal, LD50, Rabbit: > 14112 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: 23,4 mg/L (4 h)
Method: OECD 403
Based on available data the classification criteria are not met.

skin corrosion/irritation; Serious eye damage/eye irritation

ethyl acetate

Eyes
Causes serious eye irritation.

propan-2-ol

Eyes
Method: OECD 405
Splashing may cause eye irritation and reversible damage.

4-methylpentan-2-one

Eyes
Causes serious eye irritation.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

1-methoxy-2-propanol

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 9 / 13

Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

ethyl acetate

Specific target organ toxicity (single exposure), drowsiness:
Inhalation causes narcotic effects/intoxication.

propan-2-ol

Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

4-methylpentan-2-one

Specific target organ toxicity (single exposure), Irritation:
Irritating to respiratory system.

Hydrocarbons, C9, aromatics

Specific target organ toxicity (single exposure), Irritation:
May cause respiratory irritation.

Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

n-butyl acetate

Specific target organ toxicity (single exposure), drowsiness:
May cause drowsiness or dizziness.

Aspiration hazard

Hydrocarbons, C9, aromatics

Aspiration hazard
May be fatal if swallowed and enters airways.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 21100 - 25900 mg/L (48 h)
Based on available data the classification criteria are not met.

ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 455 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 717 mg/L (48 h)
Algae toxicity, ErC50, Scenedesmus subspicatus: 5600 mg/L (48 h)
Based on available data the classification criteria are not met.

propan-2-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 9640 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 9714 mg/L (48 h)
Algae toxicity, ErC50, Scenedesmus quadricauda: > 1000 mg/L (72 h)
Bacteria toxicity: > 100 mg/L

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 10 / 13

Based on available data the classification criteria are not met.

4-methylpentan-2-one

Fish toxicity, LC50: > 179 mg/L (96 h)
Method: OECD 202
Daphnia toxicity, EC50, Daphnia magna: > 200 mg/L (48 h)
Method: OECD 202
Bacteria toxicity, EC50, Pseudomonas putida: 275 mg/L (16 h)
Based on available data the classification criteria are not met.

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss: 9,2 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3,2 mg/L (48 h)
Method: OECD 202
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 2,6 - 2,9 mg/L (72 h)
Based on available data the classification criteria are not met.

n-butyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 18 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/L (48 h)
Algae toxicity, EC50, Desmodesmus subspicatus.: 647,7 mg/L (72 h)
Based on available data the classification criteria are not met.

Long-term Ecotoxicity

1-methoxy-2-propanol

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h)
Based on available data the classification criteria are not met.

ethyl acetate

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 2,4 mg/L (21 d)
Method: DIN 38412 / part 11
Algae toxicity, NOEC, Desmodesmus subspicatus.: > 100 mg/L (72 h)
Method: OECD 201.
Based on available data the classification criteria are not met.

4-methylpentan-2-one

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 30 - 35 mg/L (21 d)
Method: OECD 211
Based on available data the classification criteria are not met.

Hydrocarbons, C9, aromatics

Fish toxicity, LC50: (96 h)
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

1-methoxy-2-propanol

Biodegradation: > 70 %
Method: DOC reduction.
Readily biodegradable (according to OECD criteria).

ethyl acetate

Biodegradation, DOC reduction.: > 70 %
Readily biodegradable (according to OECD criteria).

propan-2-ol

Biodegradation: 53 % (5 d)
Readily biodegradable (according to OECD criteria).

4-methylpentan-2-one

Biodegradation.: 83 % (28 d)
Method: OECD 301 F
Readily biodegradable (according to OECD criteria).

Hydrocarbons, C9, aromatics

Biodegradation:
Readily biodegradable (according to OECD criteria).

n-butyl acetate

Biodegradation, aerobic: 83 % (28 d)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 11 / 13

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

dimethyl ether

Distribution coefficient (n-octanol / water) (log P O/W): < 4

1-methoxy-2-propanol

Distribution coefficient (n-octanol / water) (log P O/W): 0,43

ethyl acetate

Distribution coefficient (n-octanol / water) (log P O/W): 0,68 - 0,73

4-methylpentan-2-one

Distribution coefficient (n-octanol / water) (log P O/W): 1,38 - 1,9

Method: OECD 117

n-butyl acetate

Distribution coefficient (n-octanol / water) (log P O/W): 2,3

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

150110 packaging containing residues of or contaminated by dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID):

Aerosols, flammable

Sea transport (IMDG):

AEROSOLS

Air transport (ICAO-TI / IATA-DGR):

Aerosols, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

n.a.

14.5. Environmental hazards

Land transport (ADR/RID)

n.a.

Marine pollutant

n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 311000
 Print date 28.04.2016
 Version 1.11

Quick Sanding Sealer
 Revision date 18.04.2016
 Issue date 18.04.2016

EN
 Page 12 / 13

tunnel restriction code D

Sea transport (IMDG)

EmS-No. F-D, S-U

14.7. **Transport in bulk according to Annex II of MARPOL and the IBC Code**
 not applicable

SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 711,594

VOC-value (in g/L) ASTM D 2369: 711,594

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. **Chemical Safety Assessment**

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
205-500-4 141-78-6	ethyl acetate	01-2119475103-46-xxxx
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35-xxxx
203-550-1 108-10-1	4-methylpentan-2-one	01-2119473980-30-xxxx
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29-xxxx
200-661-7 67-63-0	propan-2-ol	01-2119457558-25-xxxx
204-065-8 115-10-6	dimethyl ether	01-2119472128-37-xxxx
918-668-5	Hydrocarbons, C9, aromatics	01-2119455851-35-xxxx

SECTION 16: Other information

Full text of classification in section 3:

Flam. Gas 1 / H220 compressed gas / H280	Flammable gases Gases under pressure	Extremely flammable gas. Contains gas under pressure; may explode if heated.
Flam. Liq. 3 / H226 STOT SE 3 / H336	flammable liquids Specific target organ toxicity (single exposure)	Flammable liquid and vapour. May cause drowsiness or dizziness.
Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 Acute Tox. 4 / H332 STOT SE 3 / H335	flammable liquids Serious eye damage/eye irritation Acute toxicity (inhalative) Specific target organ toxicity (single exposure)	Highly flammable liquid and vapour. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.
Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	Aspiration hazard Hazardous to the aquatic environment	May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 311000
Print date 28.04.2016
Version 1.11

Quick Sanding Sealer
Revision date 18.04.2016
Issue date 18.04.2016

EN
Page 13 / 13



guaranteed attributes of the product.