

Intended Use

- A high build primer serving, for instance, as sealing primer in case of new constructions, as blocking primer in case of repairs or as smoothing primer for closed-porous surfaces.
- Suitable for light and dark woods.
- Recommended for indoor use.

Characteristics

- A transparent lacquer based on nitrocellulose.
- Gloss level: matt.
- Sandable after approx. 20 minutes.
- Little colour-intensifying effect.
- Overcoatable with all König touch-up and spray lacquers.

Application Notes

Shake can well before use (rattle of mixing balls must be heard) and spray briefly to clear the valve. Prior to use, make a test on an inconspicuous area first, as product is not Soft-PVC resistant. Process at room temperature – do not spray onto cold, hot or damp surface.

In case of **horizontal** surfaces, sand and remove sanding dust before applying a wet coat.

For **vertical** surfaces, several (2-3) coats, not too wet, are best.

Spray distance approx. 30 cm.

After approx. 20 minutes, at normal room temperature, strip off upper lacquer pimples using the Special Scraper or 280-320 grit sandpaper.

After the second priming process, sand with 240/280 grit Dry Sandpaper and treat with Wire Wool. Finally, remove sanding dust thoroughly.

Physical Properties and Shelf Life

- Sandable:** after approx. 20 minutes
(dependent on room temperature and coat thickness)
- Substrate material:** real wood, veneer, plywood and MDF-boards
- Coverage:** approx. 1.5 m² per 400 ml, if applied twice
- Shelf life:** minimum 2 years
(stored upright at room temperature, in unopened original container)

Safety Precautions

Please refer to label and material safety data sheet.

Disposal

- Dispose of König aerosol cans in accordance with legal requirements only, when completely empty. For further information, please contact your local waste industry office.
- Leftover material to be disposed of in accordance with EWC 150110 (packaging containing residues of or contaminated by dangerous substances).
- Heinrich König & Co. KG take care of the disposal of Sprüh-König aerosol cans, provided they are returned 'carriage paid' to the address stated below.

Packaging

On request.

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Seit 1892

Heinrich König ; a V< ' & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

2021.43