

König Acrylic Lacquer ProSi 360-365

Intended Use

- A high build lacquer for new and re-lacquering.
- Especially suitable for outdoor use, even if silicone-containing sealing agents have been used.
- To be used indoor, when lightfastness and moisture resistance are highly requested.
- A mobile spray system for the re-lacquering of partial and entire areas.

Characteristics

- A colourless combination lacquer based on acrylic. Physically drying system.
- Good crosslinking and running properties with excellent hardness and resistance.
- Prevents formation of an orange-peel effect.
- Lightfast and weather resistant.
- Will not yellow after having cured, ring and abrasion resistant.
- Limited PVC-resistance (window and door gaskets).

Application Notes

Shake can well before use. When banging of the mixing balls is audible – still shake at least for another 20 seconds. 'Gloss' and 'High-Gloss' do not contain mixing balls. Process at room temperature – do not spray on cold surface. Lightly sand area to be treated with 240/280 grit Dry Sandpaper 414 to level abrasions. Then sand carefully either with Wire Wool 000, 413 or with the 1500 grit Sanding Pad 609 and remove sanding dust thoroughly.

In case of vertical surfaces, several (2-3) coats, not too wet, are best. Allow 15 minutes flash-off time between each coat.

Prior to use, make a test spray on an inconspicuous area, to check lacquer compatibility.

Physical Properties and Shelf Life

Drying periods (at 20°C RT)

Dust-dry:	after 15-20 minutes
Touch-proof:	after 30 minutes
Lightfast:	from good up to very good
Weather resistant:	from good up to very good
Coverage:	approx. 2 m ² per 400 ml (single application)
Shelf life:	minimum 2 years (stored upright at room temperature, in unopened original container)

Safety Precautions

- Irritant.
- Irritating to eyes, skin and respiratory system.
- Extremely flammable.
- Pressurized container.
- Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Do not spray on a naked flame or any incandescent material.
- Keep away from sources of ignition – No smoking.
- Do not spray into eyes.
- Keep out of reach of children.

Extract of wordings of the law. For further information, please see label and Material Safety Data Sheet.

Disposal

- Dispose of König aerosol cans in accordance with legal requirements only, when completely empty. For further information, please ask your local waste industry office.
- Leftover material to be disposed of according to the European Waste Code 160504 – *gases in pressure containers containing dangerous substances*.
- Heinrich König & Co. KG take care of the disposal of Sprüh-König aerosol cans, provided they are returned 'carriage paid' to the address stated below.

Packaging

150 ml/400 ml Sprüh-König aerosol can
Gloss levels: deep matt (360), matt (361), silk matt (362), silk gloss (363), gloss (364), high-gloss (365)

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



®
Seit 1892
Heinrich König & Co. KG
An der Rosenhelle 5 • D-61138 Niederdorfelden
Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11
E-mail: info@heinrich-koenig.de

Issue 41/08