

König PF Covering Lacquer

372 000

Intended Use

- For an opaque dyeing, especially for wood and plastic surfaces in the plain colour sector.
- A mobile spray system for the coloured re- and new lacquering of repaired and partial areas.
- For indoor and outdoor use.

Characteristics

- A pigmented acrylic-based covering lacquer.
- Dries rapidly.
- High opacity.
- Overcoatable with all König touch-up and aerosol lacquers.
- Good adhesion to many varnished and plastic surfaces (not to Soft-PVC).
- Limited PVC-resistance (door and window gaskets).
- Good lightfastness and weather-resistance (adequate coat thickness required!).

Application Notes

Shake can well and spray briefly to clear the valve. When banging of the mixing balls is audible – shake at least for another 30 seconds. Repeat this operation during processing. Process at room temperature – do not spray on cold, hot or damp surfaces. Do not use in the gasket area of windows and doors.

Sand area to be treated with 240/280 grit Dry Sandpaper first, to level off scratches and abrasions. Final sanding either with Wire Wool 000 or with the 1500 grit Sanding Pad. Remove sanding dust thoroughly. With vertical surfaces, apply several thin coats. Allow for a 20 minutes flash-off time between each coat.

Finally, adjust any sheen level deviation by misting with Special Repair Lacquer PLUS.

Note: The larger the spray distance, the 'finer' the lacquer application (less gloss). The smaller the spray distance, the 'wetter' the lacquer application (more gloss) – this extends the drying time.

Physical Properties and Shelf Life

Processing recommended: at 18-25°C and 55-65% RH
Dust-dry: after approx. 15-20 minutes
Touch-proof: after approx. 30 minutes (dependent on room temperature and coat thickness)
Coverage: approx. 2 m² per 400 ml (single application)
Lightfastness: good
Weather resistance: good
Shelf life: minimum 2 years (stored upright at room temperature, in unopened original container)

Safety Precautions

Please refer to label and material safety data sheet.

Disposal

- Dispose of König aerosol cans in accordance with legal requirements only, when completely empty. For further information, please ask your local waste industry office.
- Leftover material to be disposed of according to the European Waste Code 150110 – *packaging containing residues of, or contaminated by, dangerous substances.*
- Heinrich König & Co. KG take care of the disposal of Sprüh-König aerosol cans, provided they are returned 'carriage paid' to the address stated below.

Packaging

On request.

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Seit 1892

Heinrich König; a V< & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

2021.43