Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 1/12 Revision: N°26 (03/12/2015)



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: Sprayshine Product code: 80301.

1.2. Relevant identified uses of the substance or mixture and uses advised against

furniture upkeep

1.3. Details of the supplier of the safety data sheet

Registered company name: INITIATIVES DECORATION.

Address: ZI DES SOEURS 20 AVENUE ANDRE DULIN BP30027.17301.ROCHEFORT CEDEX.France.

Telephone: +(33)-05-46-88-88-00. Fax: +-(33)-05-46-88-88-01.

contact@groupe-id.com http://www.id-paris.com

1.4. Emergency telephone number: 01-45-42-59-59.

Association/Organisation: ORPHILA.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02 GHS07

Signal Word : DANGER

Product identifiers:

EC 919-857-5 NAPHTA LOURD HYDROTRAITE

650-002-00-6 TURPENTINE, OIL

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 2/12 Revision: N°26 (03/12/2015)

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Storage:

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: 649_327_00_6	GHS07, GHS08, GHS02	[1]	25 <= x % < 50
CAS: 64742-48-9	Dgr		
EC: 919-857-5	Flam. Liq. 3, H226		
REACH: 01-2119463258-33	Asp. Tox. 1, H304		
	STOT SE 3, H336		
NAPHTA LOURD HYDROTRAITE	EUH:066		
INDEX: 601_004_00_0	GHS02	C	25 <= x % < 50
CAS: 106-97-8	Dgr	[1]	
EC: 203-448-7	Flam. Gas 1, H220	[7]	
REACH: 01-2119474691-32	Press. Gas, H280		
BUTANE			
INDEX: A609	GHS07, GHS09, GHS08, GHS02		$25 \le x \% \le 50$
CAS: 64742-49-0	Dgr		
EC: 921-024-6	Flam. Liq. 2, H225		
REACH: 01-2119475514-35	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
HYDROCARBURES,C6-C7,N ALCANES,	STOT SE 3, H336		
ISOALCANES, CYCLIQUES<5% N HEXANE	Aquatic Chronic 2, H411		
INDEX: 650-002-00-6	GHS02, GHS08, GHS07, GHS09	[1]	2.5 <= x % < 10
CAS: 8006-64-2	Dgr		
EC: 232-350-7	Flam. Liq. 3, H226		
REACH: 01-2119553060-53-0011	Acute Tox. 4, H332		
	Acute Tox. 4, H312		
TURPENTINE, OIL	Acute Tox. 4, H302		
	Asp. Tox. 1, H304		
	Eye Irrit. 2, H319		
	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Aquatic Chronic 2, H411		

(Full text of H-phrases: see section 16)

Information on ingredients:

- [7] Propellant gas
- [1] Substance for which maximum workplace exposure limits are available.

Sprayshine - 80301

Date: 06/08/2021 Page 3/12 Revision: N°26 (03/12/2015)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Sprayshine - 80301

Date: 06/08/2021 Page 4/12 Revision: N°26 (03/12/2015)

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Sprayshine - 80301

Date: 06/08/2021 Page 5/12 Revision: N°26 (03/12/2015)

Do not breathe in aerosols.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- France (INRS - ED984 / 2020-1546):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
106-97-8	800	1900	-	-	-	-
8006-64-2	100	560	-	-	-	65.84

- Switzerland (SUVAPRO 2019):

CAS	VME	VLE	Valeur plafond	Notations
64742-48-9	50 ppm	100 mg/m ³		
	300 mg/m ³	600 fc/m ³		
106-97-8	800 ppm	3200 mg/m ³		
	1900 mg/m ³	7600 fc/m ³		
8006-64-2	20 ppm	40 mg/m ³		
	112 mg/m ³	224 fc/m³		

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
106-97-8	600 ppm	750 ppm		Carc	
	1450 mg/m3	1810 mg/m3			
8006-64-2	100 ppm	150 ppm			
	566 mg/m ³	850 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

HYDROCARBURES, C6-C7, N ALCANES, ISOALCANES, CYCLIQUES < 5% N HEXANE (CAS: 64742-49-0)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 773 mg/kg body weight/day

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 6/12 Revision: N°26 (03/12/2015)

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 2035 mg of substance/m3

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 208 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 871 mg of substance/m3

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):









Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties:

- Impervious gloves in accordance with standard EN ISO 374-2

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Type of FFP mask:

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category:

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

Particle filter according to standard EN143:

- P1 (White)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state : Fluid liquid.

Spray.

Date: 06/08/2021 Page 7/12 Revision: N°26 (03/12/2015)

Important health, safety and environmental information

pH: Not relevant.

Boiling point/boiling range: Not specified.

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density: = 1

Water solubility: Insoluble.

Viscosity:v < 7 mm2/s (40°C)Melting point/melting range :Not specified.Self-ignition temperature :Not specified.Decomposition point/decomposition range :Not specified.Chemical combustion heat :>= 30 kJ/g.

9.2. Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 8/12 Revision: N°26 (03/12/2015)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity:

BUTANE (CAS: 106-97-8)

Inhalation route (n/a): LC50 = 658 ppmSpecies: Rat

HYDROCARBURES, C6-C7, N ALCANES, ISOALCANES, CYCLIQUES < 5% N HEXANE (CAS: 64742-49-0)

Oral route : LD50 > 5000 mg/kg

Species: Rat

Dermal route: LD50 > 2000 mg/kg

Species: Rabbit

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route: LD50 > 2000 mg/kg

Species: Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a): LC50 5000

Germ cell mutagenicity:

BUTANE (CAS: 106-97-8)

No mutagenic effect.

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

No mutagenic effect.

Carcinogenicity:

BUTANE (CAS: 106-97-8)

Carcinogenicity Test: Negative.

No carcinogenic effect.

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Carcinogenicity Test: Negative.

No carcinogenic effect. Species: Mouse

OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Reproductive toxicant:

BUTANE (CAS: 106-97-8) No toxic effect for reproduction

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

No toxic effect for reproduction

Specific target organ systemic toxicity - repeated exposure :

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

EPA OPPTS 870.3200 (Repeated Dose Dermal Toxicity -21/28 Days)

Date: 06/08/2021 Page 9/12 Revision: N°26 (03/12/2015)

Inhalation route: C 11.6

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Fish toxicity: LC50 > 1000 mg/l

Species : Oncorhynchus mykiss Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 > 1000 mg/l

Species : Daphnia magna Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity: ECr50 > 1000 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

NOEC = 100 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HYDROCARBURES, C6-C7, N ALCANES, ISOALCANES, CYCLIQUES < 5% N HEXANE (CAS: 64742-49-0)

Biodegradability: Rapidly degradable.

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Biodegradability: Rapidly degradable.

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 10/12 Revision: N°26 (03/12/2015)

12.3. Bioaccumulative potential

12.3.1. Substances

HYDROCARBURES, C6-C7, N ALCANES, ISOALCANES, CYCLIQUES < 5% N HEXANE (CAS: 64742-49-0)

Octanol/water partition coefficient : log Koe < 4.6

NAPHTA LOURD HYDROTRAITE (CAS: 64742-48-9)

Octanol/water partition coefficient : log Koe = 5

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification:



2.1

14.4. Packing group

. . . .

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344	E0	2	D
							625			

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 11/12 Revision: N°26 (03/12/2015)

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	2	See SP63	-	See SP277	F-D,S-U	63 190 277	E0
						327 344 381	
						959	

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167	E0
							_	A802	
	2.1	-	-	Forbidden	Forbidden	-	-	A1 A145 A167	E0
								A802	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Version: N°2 (03/08/2018) INITIATIVES DECORATION

Sprayshine - 80301

Date: 06/08/2021 Page 12/12 Revision: N°26 (03/12/2015)

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations:

DNEL : Derived No-Effect Level STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.